

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 1/13/2022 Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : S-18 All Purpose Cement
Synonyms : Polychloroprene Adhesive Blend/Compound

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives
Restrictions on use : No additional information available

1.3. Supplier

Supplier

RH Products Co., Inc.
308 Old High Street
Acton, MA 01720 - USA
T 1-978-897-8000
sales@rhadhesives.com

1.4. Emergency telephone number

Emergency number : 1-800-535-5053 INFOTRAC; 1-352-323-3500 INFOTRAC International

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 2	H225	Highly flammable liquid and vapor
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Germ cell mutagenicity Category 2	H341	Suspected of causing genetic defects
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336	May cause drowsiness or dizziness
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment - Acute Hazard Category 1	H400	Very toxic to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 1	H410	Very toxic to aquatic life with long lasting effects

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)

H336 - May cause drowsiness or dizziness
H341 - Suspected of causing genetic defects
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H410 - Very toxic to aquatic life with long lasting effects

: P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical, lighting, ventilating equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P260 - Do not breathe vapors, mist, spray.
P264 - Wash hands and forearms, and other exposed area thoroughly after handling.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use dry extinguishing powder, alcohol resistant foam, carbon dioxide (CO2) to extinguish.
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P235 - Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to in accordance with all local, regional, national and international regulations.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Product identifier	%	GHS US classification
n-heptane	CAS-No.: 142-82-5	≥ 25 – < 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Toluene	CAS-No.: 108-88-3	≥ 25 – < 40	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 3, H412
Component A	CAS-No.: trade secret	≥ 15 – < 20	Muta. 2, H341
Ethyl acetate	CAS-No.: 141-78-6	≥ 5 – < 10	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Acetone	CAS-No.: 67-64-1	≥ 5 – < 10	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Component C	CAS-No.: trade secret	≥ 1 – < 2.5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1B, H317 STOT SE 3, H335
Component B	CAS-No.: trade secret	≥ 1 – < 2.5	Not classified

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center/doctor/physician if you feel unwell. Never give anything by mouth to an unconscious person.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.
Symptoms/effects after skin contact	: Causes skin irritation. May produce an allergic reaction. Redness. Itching. Skin rash/inflammation. Absorbed through the skin. Repeated exposure may cause skin dryness or cracking.

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after eye contact	: Causes serious eye irritation. Lacrimation. Redness. Blurred vision.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure. May cause kidney and liver disease, and disorders of the central nervous system.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Alcohol-resistant foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard	: Highly flammable liquid and vapor. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Heating will cause a rise in pressure with a risk of bursting. In case of fire and/or explosion do not breathe fumes.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon dioxide. Carbon monoxide.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions	: Move containers from fire area if it can be done without personal risk. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Use water spray or fog for cooling exposed containers. Prevent fire-fighting water from entering environment. Evacuate the danger area. Eliminate all ignition sources if safe to do so.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin and eyes. No flames, no sparks. Eliminate all sources of ignition. Use special care to avoid static electric charges.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Do not touch or walk on the spilled product. Do not get in eyes, on skin, or on clothing. Avoid breathing vapors, fume. Evacuate unnecessary personnel. No action shall be taken without appropriate training or involving any personal risk.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Avoid breathing (dust, vapor, mist, gas). Use non-sparking tools.

6.2. Environmental precautions

Avoid release to the environment. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Notify authorities if product enters sewers or public waters.

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak, if possible without risk. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Remove ignition sources.
- Methods for cleaning up : Caution : this product can cause the floor to be slippery. Move containers from spill area. Prevent entry to sewers and public waters. Small quantities of liquid spill: take up in non-combustible absorbent material and shovel into container for disposal. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Clean contaminated surfaces with an excess of water. Use non-sparking tools.
- Other information : Dispose of via an authorised person/ licensed waste disposal contractor or by other suitable waste treatment techniques.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapor concentrations. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing fume, vapors, mist. Eliminate all ignition sources if safe to do so. Handling this product may result in electrostatic accumulation. Use proper grounding procedures. Take precautionary measures against static discharge. Use explosion-proof equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Always wash hands after handling the product. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Store in a dry place. Keep cool. Keep away from food, drink and animal feedingstuffs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store in accordance with local, regional, national or international regulation.
- Incompatible products : Strong acids. Strong bases. Oxidizing agent.
- Incompatible materials : Direct sunlight. Sources of ignition.
- Storage area : Store in dry, cool, well-ventilated area.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

S-18 All Purpose Cement	
No additional information available	
Acetone (67-64-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Acetone
ACGIH OEL TWA [ppm]	250 ppm
ACGIH OEL STEL [ppm]	500 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)	
Regulatory reference	ACGIH 2021
USA - OSHA - Occupational Exposure Limits	
Local name	Acetone
OSHA PEL (TWA) [1]	2400 mg/m ³
OSHA PEL (TWA) [2]	1000 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
n-heptane (142-82-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Heptane, isomers (n-Heptane)
ACGIH OEL TWA [ppm]	400 ppm
ACGIH OEL STEL [ppm]	500 ppm
Remark (ACGIH)	TLV® Basis: CNS impair; URT irr
Regulatory reference	ACGIH 2021
USA - OSHA - Occupational Exposure Limits	
Local name	Heptane (n-Heptane)
OSHA PEL (TWA) [1]	2000 mg/m ³
OSHA PEL (TWA) [2]	500 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
Component C (trade secret)	
No additional information available	
Component B (trade secret)	
No additional information available	
Component A (trade secret)	
No additional information available	
Toluene (108-88-3)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Toluene
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: CNS, visual & hearing impair; female repro system eff; pregnancy loss. Notations: OTO; A4 (Not classifiable as a Human Carcinogen); BEI
Regulatory reference	ACGIH 2021
USA - OSHA - Occupational Exposure Limits	
Local name	Toluene
OSHA PEL (TWA) [2]	200 ppm
OSHA PEL C [ppm]	300 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm 10 mins.

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-2
Ethyl acetate (141-78-6)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethyl acetate
ACGIH OEL TWA [ppm]	400 ppm
Remark (ACGIH)	TLV® Basis: URT & eye irr
Regulatory reference	ACGIH 2021
USA - OSHA - Occupational Exposure Limits	
Local name	Ethyl acetate
OSHA PEL (TWA) [1]	1400 mg/m ³
OSHA PEL (TWA) [2]	400 ppm
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1

8.2. Appropriate engineering controls

Appropriate engineering controls	: Provide local exhaust or general room ventilation. Handle in accordance with good industrial hygiene and safety procedures. Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Environmental exposure controls	: Avoid release to the environment. Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Wear recommended personal protective equipment. Personal protective equipment should be chosen according to the NIOSH standards and in discussion with the supplier of the protective equipment.

Hand protection:

Chemical resistant gloves (according to NIOSH standard). Please follow the instructions related to the permeability and the penetration time provided by the manufacturer. Selection of protective gloves should be made based on the type of task performed

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing. Skin protection appropriate to the conditions of use should be provided

Respiratory protection:

Where excessive vapor, mist, or dust may result, use approved respiratory protection equipment. All respirators must conform to specifications for efficiency and performance indicated by OSHA Standard 29 CFR 1910.134 and NIOSH Standards

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: Off-white
Odor	: characteristic solvent-like

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 35 °C (95.0 °F)
Flash point	: -7.78 °C (18.0 °F; Method: ASTM D-56)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: 180 mm Hg (20 °C; 68 °F)
Relative vapor density at 20 °C	: > 1 (heavier than air)
Relative density	: 0.87 (water=1)
Solubility	: insoluble in water.
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: Lower explosive limit (LEL): 1 vol % Upper explosive limit (UEL): 12 vol %
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content : 75.7 % (5.32 lbs/gal or 638 g/l)

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor. Can form explosive mixtures with air. Heating may cause a fire or explosion.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization: Will not occur. Reacts vigorously with strong oxidizers and acids.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Protect from sunlight. Overheating. Extremely high or low temperatures. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agent. Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	15688 mg/kg
LC50 Inhalation - Rat	44 g/m ³
ATE US (oral)	5800 mg/kg body weight
ATE US (dermal)	15688 mg/kg body weight
ATE US (vapors)	44 mg/l/4h
ATE US (dust, mist)	44 mg/l/4h

n-heptane (142-82-5)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 Inhalation - Rat	103 g/m ³ (4 h)

Component A (trade secret)	
LD50 oral rat	> 40000 mg/kg

Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 Inhalation - Rat	25.7 mg/l/4h
ATE US (oral)	2600 mg/kg body weight
ATE US (dermal)	12000 mg/kg body weight
ATE US (vapors)	25.7 mg/l/4h
ATE US (dust, mist)	25.7 mg/l/4h

Ethyl acetate (141-78-6)	
LD50 oral rat	5620 mg/kg
LD50 dermal rabbit	> 20 ml/kg
ATE US (oral)	5620 mg/kg body weight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: Not classified

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause drowsiness or dizziness.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: Depression of the central nervous system, headaches, dizziness, drowsiness, loss of coordination.

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/effects after skin contact	: Causes skin irritation. May produce an allergic reaction. Redness. Itching. Skin rash/inflammation. Absorbed through the skin. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye irritation. Lacrimation. Redness. Blurred vision.
Symptoms/effects after ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Abdominal pain.
Chronic symptoms	: Suspected of damaging fertility. Suspected of damaging the unborn child. Suspected of causing genetic defects. May cause damage to organs through prolonged or repeated exposure. May cause kidney and liver disease, and disorders of the central nervous system.
Other information	: No experimental study on the product is available. The information given is based on our knowledge of the components and the classification of the product is determined by calculation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

Acetone (67-64-1)	
LC50 - Fish [1]	4144.846 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 - Crustacea [1]	1679.66 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [Static])
EC50 - Crustacea [2]	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
n-heptane (142-82-5)	
LC50 - Fish [1]	375 mg/l (Exposure time: 96 h - Species: Cichlid fish)
Toluene (108-88-3)	
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC chronic crustacea	0.74 mg/l (Ceriodaphnia dubia)
Ethyl acetate (141-78-6)	
LC50 - Fish [1]	220 – 250 mg/l Pimephales promelas
EC50 - Crustacea [1]	560 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 - Fish [2]	484 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
NOEC (chronic)	Daphnia magna, 21d

12.2. Persistence and degradability

S-18 All Purpose Cement	
Persistence and degradability	Biodegradability in water: no data available.
Acetone (67-64-1)	
Persistence and degradability	Readily biodegradable.

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

S-18 All Purpose Cement

Bioaccumulative potential	No data available concerning bioaccumulation.
---------------------------	---

Acetone (67-64-1)

BCF - Fish [1]	0.69
----------------	------

Partition coefficient n-octanol/water (Log Pow)	-0.24
---	-------

n-heptane (142-82-5)

Partition coefficient n-octanol/water (Log Pow)	4.66
---	------

Toluene (108-88-3)

Partition coefficient n-octanol/water (Log Pow)	2.65
---	------

Ethyl acetate (141-78-6)

BCF - Fish [1]	30
----------------	----

Partition coefficient n-octanol/water (Log Pow)	0.6
---	-----

12.4. Mobility in soil

S-18 All Purpose Cement

Ecology - soil	Adsorbs into the soil.
----------------	------------------------

12.5. Other adverse effects

Other adverse effects : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Do not dispose of the packaging without first carrying out the necessary cleaning. Do not pierce or burn, even after use.
Additional information	: Flammable vapors may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with Department of Transport / Transportation of Dangerous Goods / IMDG / IATA

14.1. UN number

DOT NA No	: UN1133
UN-No. (TDG)	: Not applicable
UN-No. (IMDG)	: 1133
UN-No. (IATA)	: 1133

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Adhesives
Proper Shipping Name (TDG)	: Not applicable
Proper Shipping Name (IMDG)	: ADHESIVES

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (IATA) : Adhesives

14.3. Transport hazard class(es)

DOT

Transport hazard class(es) (DOT) : 3

Hazard labels (DOT) : 3



TDG

Transport hazard class(es) (TDG) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : 3

Hazard labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3



14.4. Packing group

Packing group (DOT) : II

Packing group (TDG) : Not applicable

Packing group (IMDG) : II

Packing group (IATA) : II

14.5. Environmental hazards

Dangerous for the environment : Yes

Marine pollutant : Yes



Other information : No supplementary information available.

14.6. Special precautions for user

DOT

UN-No.(DOT) : UN1133

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	:	149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons). 383 - Packages containing toy plastic or paper caps for toy pistols described as "UN0349, Articles, explosive, n.o.s. (Toy caps), 1.4S" or "NA0337, Toy caps, 1.4S" are not subject to the subpart E (labeling) requirements of this part when offered for transportation by motor vehicle, rail freight, cargo vessel, and cargo aircraft and, notwithstanding the packing method assigned in §173.62 of this subchapter, in conformance with the following conditions: B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks. IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized. T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
DOT Packaging Exceptions (49 CFR 173.xxx)	:	150
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	173
DOT Packaging Bulk (49 CFR 173.xxx)	:	242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	60 L
DOT Vessel Stowage Location	:	B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

TDG

Emergency Response Guide (ERG) Number : 128

IMDG

Limited quantities (IMDG)	:	5 L
Excepted quantities (IMDG)	:	E2
Packing instructions (IMDG)	:	P001
Packing provisions (IMDG)	:	PP1
IBC packing instructions (IMDG)	:	IBC02
Tank instructions (IMDG)	:	T4
Tank special provisions (IMDG)	:	TP1, TP8
EmS-No. (Fire)	:	F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage)	:	S-D - SPILLAGE SCHEDULE Delta - FLAMMABLE LIQUIDS
Stowage category (IMDG)	:	B
Properties and observations (IMDG)	:	Adhesives are solutions of gums, resins, etc., usually volatile due to the solvents. Miscibility with water depends upon their composition.

IATA

PCA Excepted quantities (IATA)	:	E2
PCA Limited quantities (IATA)	:	Y341
PCA limited quantity max net quantity (IATA)	:	1L
PCA packing instructions (IATA)	:	353
PCA max net quantity (IATA)	:	5L
CAO packing instructions (IATA)	:	364
CAO max net quantity (IATA)	:	60L
Special provision (IATA)	:	A3
ERG code (IATA)	:	3L

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Component C	CAS-No. trade secret	≥ 1 – < 2.5%
Component B	CAS-No. trade secret	≥ 1 – < 2.5%
Component A	CAS-No. trade secret	≥ 15 – < 20%
Ethyl acetate	CAS-No. 141-78-6	≥ 5 – < 10%

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Toluene	CAS-No. 108-88-3	≥ 25 – < 40%
---------	------------------	--------------

Acetone (67-64-1)

CERCLA RQ	5000 lb
-----------	---------

Toluene (108-88-3)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ	1000 lb
-----------	---------

15.2. International regulations

CANADA

Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

n-heptane (142-82-5)

Listed on the Canadian DSL (Domestic Substances List)

Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

No additional information available

S-18 All Purpose Cement

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations



WARNING:

California Proposition 65

This product can expose you to Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources : Supplier's safety documents.
Training advice : Training staff on good practice.
Other information : SDS prepared by. H2 Compliance.

Full text of H-phrases	
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.