

HH-66 Vinyl Cement

DIRECTIONS

1. Clean surfaces with alcohol or compatible solvent.
2. Sand any glossy surfaces lightly.
3. Apply an even coat to both surfaces to be joined.
4. Allow cement to set for 2-5 minutes or until tacky.
5. Press together and allow to bind before use.
6. Remove any excess adhesive.

Apply within 18 months of manufacture for best results.

DANGER



Highly flammable liquid and vapour. Causes serious eye irritation.
May cause drowsiness or dizziness.

HAZARDOUS INGREDIENTS: Methyl Ethyl Ketone 78-93-3, Acetone 67-64-1, Toluene 108-88-3

PREVENTION:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist, vapours, spray. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection.

RESPONSE:

IF ON SKIN (or hair):

Take off immediately all contaminated clothing. Rinse skin with water (or shower).

IF INHALED:

Remove person to fresh air and keep comfortable for breathing.

IF IN EYES:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

DISPOSAL:

Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

See SDS for further details regarding the safe use of this product.

Emergency Number: INFOTRAC +1-352-323-3500